## **IN THE CLAIMS**:

Please AMEND claims 1, 3-5, 7, 9-11, and 13-14; and Please ADD claims 15-18, as shown below.

1. (Currently Amended) A data transmission method-in a telecommunication system, the method comprising:

employing a packet protocol for data transmission;

identifying at least some participants of the <u>data</u> transmission with internet protocol addresses;

activating a packet data context for data transmission between <u>identified</u> participants;

associating one packet data context with more than one internet protocol addresses; and

transmitting data between the identified participants.

- 2. (Previously Presented) The method of claim 1, further comprising: activating the packet data context in a mobile station.
- 3. (Currently Amended) The method of claim 1, further comprising:

identifying one or more units of terminal equipment with unique internet protocol addresses, the terminal equipment being connected to a mobile termination of the mobile station—; and

identifying the mobile termination with a unique internet protocol address.

4. (Currently Amended) The method of claim 3, further comprising:
the mobile termination sending packet data from more than one internet addresses
using one packet data context.

5. (Currently Amended) The method of claim 3, further comprising:
the mobile termination receiving packet data associated with more than one
internet addresses,; and

forwarding each packet to the terminal equipment with the respective internet address.

6. (Previously Presented) The method of claim 1, further comprising:

activating the packet data context between a mobile station and a gateway support

node.

- 7. (Currently Amended) The method of claim 1, further comprising: transferring data between a mobile station and a gateway support node relating to more than one internet addresses using one packet data context.
  - 8. (Previously Presented) The method of claim 1, further comprising: activating one packet data context for each quality of service in use.
- 9. (Currently Amended) The method of claim 3, further comprising:
  the mobile termination sending a request to the network for a new internet address,
  when new terminal equipment is connected to the mobile termination; and
  associating the internet address with the packet data context.
- 10. (Currently Amended) The method of claim 3, further comprising:
  the mobile termination sending a request to the network to release the internet
  address of terminal equipment, when the terminal equipment is disconnected from the
  mobile termination; and

disassociating the internet address from the packet data context.

- 11. (Currently Amended) A telecommunication system, comprising:
- a first unit; and
- a second unit,

wherein the first unit and the second unit are arranged configured to communicate with each other using a packet protocol for data transmission; where in

wherein at least some participating units of the transmission are identified with internet protocol addresses;

wherein the first and the second unit are arranged configured to activate a packet data context for data transmission between the units, wherein and

wherein the first <u>unit</u> and the second unit are <u>arrangedconfigured</u> to associate one packet data context for more than one internet protocol addresses.

- 12. (Previously Presented) The system of claim 11, wherein the first unit comprises a mobile termination and one or more units of terminal equipment, each identified by a different internet protocol address.
- 13. (Currently Amended) The system of claim 12, wherein the second unit is a gateway support node, and that the gateway support node and the mobile termination are arranged configured to activate a packet data context, and to use the packet data context in the data transmission relating to more than one internet addresses.
- 14. (Currently Amended) The system of claim 11, wherein the system is arranged configured to support connections with a different quality of service, and the

first and the second unit are <u>arranged\_configured</u> to activate one packet data context for each quality of service.

15. (New) An apparatus, comprising:

a plurality of transmission units,

wherein the plurality of transmission units are configured to communicate using a single packet data context, and

wherein each of the plurality of transmission units has a unique internet protocol address.

16. (New) An apparatus, comprising:

a plurality of transmission means for communicating information in a communications network,

wherein the plurality of transmission means are configured to communicate using a single packet data context, and

wherein each of the plurality of transmission means has a unique internet protocol address.

17. (New) The method of claim 1, wherein the associating one packet data context with more than one internet protocol address comprises associating one packet data context with more than one internet protocol address of a same type to one another.

18. (New) The system of claim 11, wherein the more than one internet protocol address comprises addresses of a same type to one another.